



# Slickline **EBW** Detonator Control (**SS-1274**)

The **Slick Shot EBW Detonator Control (SS-1274)** is an electronic perforating tool that provides control of slickline conveyed downhole detonation operations through a **RF Safe EBW Detonator**. This multi-functional tool controls and initiates RF Safe EBW Detonators for various types of **perforating guns, explosive cutters, bridge plugs, cement retainers, dump bailers** and other devices. Superior safety design features, controlled by a microprocessor and redundant lockouts, give the user the peace-of-mind that the **SS-1274** is “The **Safe And Smart Trigger**” for explosive operations.

### SAFETIES / Controls / Benefits

- ◆ Three (3) Primary Safeties to **Safely** Shoot Guns and Perforate
- ◆ No Computer Required for Programming
- ◆ Switch Selectable Time & Temperature Programming
- ◆ Smart Running Gear Protects the tool from Shock
- ◆ Audible signal to indicate tool operation and status
- ◆ Initiates RF Safe EBW Detonators through control of the ECOSSE OM-1 Fire Set

Operating Temperature	32°F to 302°F (0°C to 150°C) **
<b>Outside Diameter</b>	<b>1.38 in. (3.5 cm)</b>
<b>Length</b>	<b>60" (1.5 m) Plus Running Gear</b>
<b>Weight</b>	<b>14 lbs. (6.4 Kg)</b>
Maximum Pressure	15,000 psi (103,000 kPa)
Accuracy	Time ± .05% Temperature ± 3°F
Power	18.4v (5 'C' cell Lithium)

\*\* 350°F Option available